

AVAILABLE WITH
4-CYLINDER
DIESEL, OR GAS/LPG
ENGINE POWER
SOURCE.



SERIOUS CLEANING DEMANDS
A TRULY PROFESSIONAL
MACHINE



2 METRES WIDE SWEEPING PATH!

The Nilfisk SR 1900 represents a huge step forward in industrial class ride-on sweepers. With its extraordinary 2 metres wide sweeping path, the SR 1900 can sweep and clean large areas, such as parking lots, warehouses, factory floors and construction sites, in a fraction of the time it takes a conventional sweeper. Moreover it does this while efficiently controlling the dust, thanks to the innovative DustGuard™ misting system. Furthermore the SR 1900 is designed with attention to details such as better safety features, easier operator control, simple maintenance and function features that provide higher productivity and a lower total cost of cleaning.

- The unique DustGuard™ feature with misting nozzles that spray a fine fog of moisture to the front and side brushes, effectively controls airborne dust for a cleaner environment.
- The main brush's 1.3 metre sweeping path is the widest in the industry, enabling better productivity through faster cleaning. Total cleaning width with side brushes is 2 metres.
- The strong polyethylene covers offer a high driving protection and even absorbing bumps up to 8 km/h. At the same time, they are fully recyclable in line with Nilfisk's environmental-awareness policy.
- The large-area operator compartment provides more comfort with less fatigue. One-Touch™ control and a clear view of the working zone give a better cleaning result with greater safety.

TECHNICALLY
SUPERIOR AND
ENVIRONMENTALLY
FRIENDLY



The exclusive DustGuard™ system effectively controls airborne dust by providing a fine mist of moisture to the front and side brushes



Operation of the SR 1900 could not be easier. One-Touch™ control shortens operator-training time and improves the cleaning result



The large wheels give a smoother ride and allow the machine to mount kerbs without difficulty



Exceptionally easy serviceability is achieved with Nilfisk's NoTools™ system. The 5-sided access to engine and hydraulic components saves time and keep down the service cost



The SR 1900 incorporates superb high-dump capability up to 152 cm from ground level

RELIABILITY IS ALSO OUR MANTRA WHEN IT COMES TO SERVICE

A Nilfisk machine functions optimally when cared for by regular service and maintenance visits. Therefore we have created the optimal service solution: four levels of service reflecting different requirements and an optional supply of a substitute machine in critical situations.

24-HOUR SERVICE

Full Service+ Solution

A total coverage package offering four maintenance visits a year + service at a known fixed cost. Optimal for customers with a need for extensive daily cleaning. Labour, travel expenses, spares and parts are all included.

Full Service Solution

A package offering four maintenance visits a year + service. Ideal for customers who clean daily. Labour, travel expenses and spares are included.

Standard Service Solution

This package provides two preventative maintenance visits a year. Labour and travel expenses are included.

Subscription Solution

By entering the subscription contract, the customer agrees to a minimum of one maintenance visit per year.

Corrosion resistant hopper has extra-high dumping capability while the integrated bumper protects against machine damage

UltraWeb™ dust filter captures even microscopic particles and is cleaned automatically. The long lasting pocket filter solution is also available

The DustGuard™ dust suppression system includes an integrated 55-litre water tank to provide an effective misting as the brushes are activated



Large operator compartment is ergonomically designed with Clear-View™ visibility for extra safety

Rust-free polyethylene covers provide excellent machine protection. They are easily removed without tools to simplify maintenance

1.3 metre main brush working width plus dual side brushes create an unprecedented 2-metre wide cleaning path.

TECHNICAL SPECIFICATIONS

Description	Unit	SR 1900 LPG	SR 1900 D
Motor power source		gas/lpg/P 4cyl 41.7Kw/56Hp	Diesel 4cyl
Motor brand	W	PSI-GM Vortec 1600	Kubota V1505D
Productivity rate 1 side broom theoretical/ actual	m ² /h	19800/13860	19800/13860
Working width with mainbroom	mm	1300	1300
Working width with right side brush	mm	1650	1650
Working width with 2 side brushes	mm	2000	2000
Min. turn-around aisle width	cm	460	460
Max. speed	km/h	15	15
Hopper volume	l	400	400
Max. dumping height	cm	152	152
Main filter area	m ²	10	10
Length x width x height	cm	239x163x147	239x163x147
Weight	kg	1225	1225

Specifications and details are subject to change without prior notice.